






Specificatii Valve Fobrite

								
Model Valva	ST / FT		SM		DM / DF		E14T / E14M	
Service @ 1 bar/15 psi	76 lpm, 4.56 m ³ /h				80 lpm, 4.8 m ³ /h		76 lpm, 4.56 m ³ /h	
Backwash @ 1.7 bar/25 psi	26 lpm, 1.56 m ³ /h				66 lpm, 4.0 m ³ /h		26 lpm, 1.56 m ³ /h	
Tanc Dedurizare	8" - 12" diametru				8" - 16" diametru		8" - 12" diametru	
Tanc Filtrare	8" - 12" diametru				8" - 16" diametru		8" - 12" diametru	
Conectori					1"			
Material Valva					Noryl			
Cicluri	7						5	
Regenerare					Downflow			
Presiune de lucru					1.4 - 8.2 bar			
Temperatura de lucru					4° - 43° C			
Limite de debit (min./max)	Nu		0.94 - 76 lpm		0.95 - 80 lpm		0.94 - 76 lpm	
Limite de volum (m ³)	Nu		8000 m ³		0.10 - 10000 m ³		0.10 - 10000 m ³	
Teava Distribuitor					1.05"			
Conexiune drenaj					1/2"			
Conexiune recipient saramura					3/8"			
Conectare valva/tanc					2 1/2" - 8 NPSM			
Inaltime de la tanc	178 mm				198 mm			
Greutate	1.7 kg		2 kg		2.4 kg		2.2 kg	
Electric	230V AC, 50Hz				230V AC, 50Hz, 24V			

Modalitate de comanda valva:

Valva Conct. Placa Programare Injector BLFC DLFC Exemplu—COD FINAL

V 1 SM M - Volumetric 1 0.5 2.4 V1SM-1-0.5-2.4

V 1 DM M - Volumetric 3 1 5 V1DM-3-1-5

Tanc - Dedurizare	Injector	Culoare	BLFC gpm	DLFC gpm
8"	1	Alb	0.125	1.5
9"	1	Alb	0.25	2-2.4
10"	1	Alb	0.5	2.4-3
12"	2	Albastru	0.5	3.5
13"	2	Albastru	0.5	4
14"	3	Galben	1	5
16"	3	Galben	1	7

NOU



Performanta Valva E14T

- Programare regenerare: Cronometrica
- Debit service @15 psi/1 bar 4.56 m³/h
- Debit spalare inversa @ 25 psi/1.7 bar 1.56 m³/h
- Regenerare cu apa tratata
- 5 cicluri de spalare cu timpi ajustabili
- Programare regenerare : 1—99zile,
- Material valva: Noryl
- Baterie Litium cu back-up 8 ore

Performanta Valva E14M

- Programare regenerare: Volumetrica
- Debit service @15 psi/1 bar 4.56 m³/h
- Debit spalare inversa @ 25 psi/1.7 bar 1.56 m³/h
- Afisare pe display: ora exacta, zile ramase pana la regenerare, volum de apa ramas pana la regenerare, volum de apa dedurizata
- Programare regenerare: Volumetric Imediat, Volumetric Intarziat, Cronometric, Saptamanal
- Regenerare cu apa tratata
- 5 cicluri de spalare cu timpi ajustabili
- Material valva: Noryl

